

jc921 U.S. PTO
09/01/00

9-5-00

H

PATENT APPLICATION TRANSMITTAL LETTER
(Large Entity)

Docket No.
END9-2000-0078-US1

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Transmitted herewith for filing under 35 U.S.C. 111 and 37 C.F.R. 1.53 is the patent application of:

Giuseppe Butturini et al.

For: **METHOD AND APPARATUS FOR IMPROVED FOLD RETENTION ON A SECURITY ENCLOSURE**

jc920 U.S. PTO
09/01/00
09/654543

Enclosed are:

- ☒ Certificate of Mailing with Express Mail Mailing Label No. **EL396832156US**
- ☒ **5** sheets of drawings.
- ☐ A certified copy of a _____ application.
- ☒ Declaration ☒ Signed. ☐ Unsigned.
- ☒ Power of Attorney
- ☒ Information Disclosure Statement
- ☐ Preliminary Amendment
- ☒ Other: **Assignment and Assignment Cover Sheet**

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	26	- 20 =	6	x \$18.00	\$108.00
Indep. Claims	5	- 3 =	2	x \$78.00	\$156.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
TOTAL FILING FEE					\$954.00

- ☐ A check in the amount of _____ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **09-0457(IBM)** as described below. A duplicate copy of this sheet is enclosed.
 - ☒ Charge the amount of **\$954.00** as filing fee.
 - ☒ Credit any overpayment.
 - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
 - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated:

Aug. 31, 2000

Lawrence R. Fraley
Signature

Lawrence R. Fraley
Reg. No. 26,885
IBM Corporation
IP Law Dept. N50/040-4
1701 North Street
Endicott, NY 13760
(607) 755-3207

cc:

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Biuseppe Butturini et al.

Serial No.:

Group Art Unit:

Filed: herewith

Examiner:

For: METHOD AND APPARATUS FOR IMPROVED FOLD RETENTION ON A SECURITY ENCLOSURE

Assistant Commissioner For Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" label number: EL396832156US

Date of Deposit: 9/01/00

I hereby certify that the following **attached** paper or fee

Patent Application
5 Sheet Drawings
Patent Application Fee Transmittal
Assignment (2 pgs., executed)
Recordation Form Cover Sheet
IDS, PTO-1449 Form, References
Declaration, (4 pgs., executed)
Express Mail Certificate
Postcard

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner For Patents, Washington, D.C. 20231.

June M. Mitchell

(Name of person mailing paper or fee)

June M. Mitchell

(Signature of person mailing paper or fee)

NOTE: Each paper must have its own certificate and the "Express Mail" label number as a part thereof or attached thereto. When, as here, the certification is presented on a separate sheet, that sheet must (1) be signed and (2) fully identify and be securely attached to the paper or fee it accompanies. Identification should include the serial number and filing date of the application as well as the type of paper being filed, e.g., complete application, specification and drawings, responses to rejection or refusal, notice of appeal, etc. If the serial number of the application is not known, the identification should include at least the name of the inventor(s) and the title of the invention.

NOTE: The label number need not be placed on each page. It should, however, be placed on the first page of each separate document, such as, a new application, amendment, assignment, and transmittal letter for a fee, along with the certificate of mailing by "Express Mail". Although the label number may be on checks, such a practice is not required. In order not to deface formal drawings, it is suggested that the label number be placed on the back of each formal drawing or the drawings be accompanied by a set of informal drawings on which the label number is placed.

Express Mail #EL396832156US

**APPLICATION
FOR
UNITED STATES LETTERS PATENT**

APPLICANT NAME: Giuseppe Butturini *et al.*

TITLE: METHOD AND APPARATUS FOR IMPROVED FOLD
RETENTION ON A SECURITY ENCLOSURE

DOCKET NO.: END9-2000-0078-US1

INTERNATIONAL BUSINESS MACHINES CORPORATION

METHOD AND APPARATUS FOR IMPROVED FOLD

RETENTION ON A SECURITY ENCLOSURE

BACKGROUND OF THE INVENTION

Technical Field

5 The present invention relates generally to the detection of intrusions into electronic assemblies, and more particularly, to the retention of a security enclosure capable of detecting such intrusions.

10 Related Art

 In electronic network commerce applications, it is a requirement to protect the contents of the associated computer systems from being unlawfully read or modified. It is conventional practice to provide certain encryption schemes in which data is transmitted and received in an encrypted form and only authorized people who have the encryption key codes may read or modify the data. However, an unauthorized person with sufficient skills and knowledge may attempt to bypass software encryption controls by making a physical attack against the computer hardware to attempt a direct interrogation of the memory components and other devices. Defense from these types of attacks requires that

tamper resistant physical packaging be provided for critical encryption components, in such a way that unauthorized attempts to gain entry are detected and encryption key codes are immediately erased.

5 One means of providing physical protection against intrusion is the use of an electrical grid surrounding the encryption module, which when broken triggers the requisite signal to disable the unit. It is known in the art to surround and protect an encryption module with a membrane consisting of one or more flexible dielectric layers having electrically conductive traces thereon. The membrane is electrically connected to the module, then wrapped, folded and bonded around the module, wherein a sticky pressure sensitive bonding adhesive adheres the membrane around the module. The traces are intentionally made fragile so that they are damaged if an attempt is made to remove the membrane. Further the membrane may be potted in a molding material, which offers further protection as its removal would also damaged the traces.

20 While the membrane must meet the physical security requirements, it must not be so sensitive that it falsely triggers the erasure of the key codes as a result of handling during the manufacturing assembly process, or subsequently due to environmental conditions associated with changes in temperature, humidity or atmospheric pressure.

Accordingly, one of the drawbacks in the current art is that the security membranes intended for wrapping, folding, and bonding to an enclosure may be too stiff to readily fold as a result of the thickness and other properties of the various layers. As a result, during the assembly folding process, a fold may be completed but the stiffness of the membrane may result in poor retention of the fold, as the elastic strain energy associated with bending the membrane overwhelms the adhesive strength of the bonding adhesive. This can result in two conditions. First, the unfolding can damage the fragile circuit traces as the adhesive pulls against them during unfolding of the membrane. Second, unfolding can produce the formation of openings or tunnels through which the subsequently applied molding materials may leak into the interior of the enclosure, resulting in the possibility of an immediate failure or potentially a reduction in reliability of the internal components.

Thus, there is a need for better means for performing the assembly wrapping, folding, and bonding operation in such a way that the membrane is not damaged, and that molding material can not subsequently leak into the interior of the enclosure. Contrary to meeting this requirement stands the fact that the available membrane materials have certain physical properties associated with their materials selection and cross-sections that can not be readily

altered, and further the fact the conductive traces are intentionally fragile so as to detect any security attack.

SUMMARY OF THE INVENTION

5 In accordance with the present invention, the first embodiment provides a method of forming a security enclosure, comprising: providing an electronic assembly; enclosing the assembly in a tamper respondent wrap, such that the wrap forms fold lines at a first and second end of the assembly; placing the enclosed assembly in a fixture, wherein the fixture comprises a base upon which the assembly rests, a first stationary arm mounted on the base holding the fold lines at the first end of the assembly, a second arm slidably mounted on the base, and a traversing mechanism to bias the second arm toward the fold lines at the second end of the assembly; and heating the enclosed assembly.

10 The second embodiment of the present invention provides a method of producing a tamper respondent enclosure, comprising: enclosing a cryptographic processor in a tamper respondent sheet, wherein an adhesive material secures the enclosure; holding the enclosed cryptographic processor such that the adhesive material remains intact; and applying heat

to the enclosed cryptographic processor to strengthen the adhesive material.

The third embodiment of the present invention provides a method of forming a security enclosure, comprising:

5 providing a circuit card; enclosing the card in a tamper respondent cloth, wherein an adhesive secures fold lines of the cloth; holding the fold lines of the cloth to maintain adhesive contact; and heating the enclosed card.

10 The fourth embodiment of the present invention provides a method of assembling a security enclosure comprising: providing a fixture; providing an enclosure having a cloth member thereon; placing the enclosure in the fixture; heating the enclosure; and removing the enclosure from the fixture.

15 The fifth embodiment of the present invention provides an apparatus for securing a security enclosure, comprising: a base upon which a security enclosure rests; a first stationary arm mounted on the base, which holds a first end of the security enclosure; a second arm slidably mounted on
20 the base; and a traversing mechanism to bias the second arm toward a second end of the security enclosure.

The foregoing and other features and advantages of the

invention will be apparent from the following more particular description of the embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The embodiments of this invention will be described in detail, with reference to the following figures, wherein like designations denote like elements, and wherein:

Fig. 1 depicts a top view of a tamper respondent wrap in accordance with the present invention;

10 Fig. 2A depicts an electronic assembly in accordance with the present invention;

Fig. 2B depicts the electronic assembly of Fig. 2A having an enclosure therearound in accordance with the present invention;

15 Fig. 3 depicts a first step in enclosing the assembly of Fig. 2A within the wrap of Fig. 1 in accordance with the present invention;

Fig. 4 depicts a second step in enclosing the assembly of Fig. 2A within the wrap of Fig. 1 in accordance with the present invention;

20 Fig. 5 depicts a third step in enclosing the assembly of Fig. 2A within the wrap of Fig. 1 in accordance with the

present invention;

Fig. 6 depicts a fourth step in enclosing the assembly of Fig. 2A within the wrap of Fig. 1 in accordance with the present invention;

5 Fig. 7 depicts a fifth step in enclosing the assembly of Fig. 2A within the wrap of Fig. 1 in accordance with the present invention;

10 Fig. 8 depicts a graph illustrating the bending modulus of the wrap of Fig. 1 in accordance with the present invention; and

Fig. 9 depicts a clamping device used in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Although certain embodiments of the present invention will be shown and described in detail, it should be understood that various changes and modifications may be made without departing from the scope of the appended claims. The scope of the present invention will in no way
20 be limited to the number of constituting components, the materials thereof, the shapes thereof, the relative arrangement thereof, etc., and are disclosed simply as an

example of the embodiment. Although the drawings are intended to illustrate the present invention, the drawings are not necessarily drawn to scale.

Referring to the drawings, Fig. 1 shows a tamper
5 respondent wrap or cloth 10 as known and used in the art. The tamper respondent cloth 10 may be a sheet of composite material similar to one made by a division of W.L. Gore (Dundee, Scotland), as described in a patent to MacPherson (US 5,858,500), which is herein incorporated by reference.
10 In particular, the tamper respondent cloth 10 comprises a laminate formed of a number of separate layers, including a delamination respondent layer, and a pierce and laser respondent layer.

The respondent layers of the tamper respondent cloth 10
15 comprise electrically responsive line elements that are disposed on a film material. The pierce and laser respondent layer is intended to detect efforts to penetrate the security enclosure by means of forming a small hole through the tamper respondent cloth 10. The delamination
20 respondent layer is intended to detect efforts to peel the tamper respondent cloth 10 away from the outer surface of the inner enclosure. The delamination respondent layer is provided with an adhesive characteristic such that peeling

it away from a surface will damage the electrically responsive materials therein. These respondent layers are adhered together by means of an adhesive. Thus the tamper respondent cloth 10 comprises respondent film layers that are bonded together with an adhesive. Moreover, an adhesive is provided to retain the folded and overlapping portions upon folding.

A top view of one such respondent layer is shown in Fig. 1. The layer includes an electrically insulating film 12, made of polyester film or other similar material, having a plurality of diagonally extending ink traces or lines 14 formed on a first and second side of the film 12 (one side shown). The lines 14 are formed by printing carbon loaded polyester ink on the surface of the film 12. The lines 14 printed on each side of the film 12 are then selectively connected at the edges 13 of the film 12. The lines 14 form a plurality of continuous conductors which break easily if attempts are made to penetrate the delamination respondent layer or the pierce and laser respondent layer.

Connection between the lines 14 and an enclosure monitor of the electronic assembly (described *infra*) is provided by an integrated ribbon cable 18. Like the lines 14, the ribbon cable 18 is formed by printing carbon loaded

polyester ink onto a first surface of the layer 12.

Connectors 16, also formed on the first surface of the layer 12, make the connection between the ribbon cable 18 and the lines 14.

5 Fig. 2A shows an electronic assembly such as a cryptographic processor card 20 in accordance with the present invention. The cryptographic processor card 20 contains an encryption module 22 which carries the secured sensitive information, a memory 24 which stores a key or code necessary to access the stored information in the encryption module 22, an erase circuit 26 which erases the stored information in the encryption module 22 in the event the tamper respondent cloth 10 around the cryptographic processor card 20 is breached, an enclosure monitor 28 which monitors the resistance of the lines 14 of the cloth 10 and activates the erase circuit 26 in the event a breach is detected, and a battery 30, all of which are mounted on a printed circuit board 32. The cryptographic processor card 20 further includes a plurality of connecting or ribbon cables 34 (one of which is shown), which are used to connect multiple enclosures to one another on a board (not shown), as known in the art.

The cryptographic processor card 20 may then be positioned inside a housing 100 comprising for example a top half 102 and a bottom half 104 of a sheet metal box, as illustrated in Fig. 2B. The two halves 102, 104 may be joined together, and include openings 106 as need to insert electrical cables into the processor card 20. The housing 100 may be designed to provide a suitable surface for wrapping the tamper respondent cloth 10.

The tamper respondent cloth 10 is then wrapped around the housing 100 containing the cryptographic processor card 20 in a manner similar to that of a gift-wrapped present, as illustrated in Fig. 3. The cloth 10 overlaps near the middle of the cryptographic processor card 20, on the underside of the card 20. The connectors 16 and ribbon cable 18 (Fig. 1) are wrapped within the cloth 10 such that the ribbon cable 18 interconnects with the enclosure monitor 28 within the enclosure.

A top flap 36 at each end of the cloth 10 is folded down over the ends 38 of the housing 100 containing the card 20 (one end 38 is shown in Fig. 4 for ease of illustration). An adhesive on the inner surface of each top flap 36 adheres each top flap 36 to the respective ends 38 for ease of assembly. As illustrated in Fig. 5, the connection cable 34

at the one end are folded upward to abut the folded top flap 36 (noting that only one end of the cryptographic processor card 20, the end nearest the encryption module 22, has the connection cable 34 extending therefrom in the current illustration, however, the present invention is not intended to be limited to the quantity nor location of the connection cable shown).

As illustrated in Fig. 6, the side flaps 40 at each end 38 of the housing 100 containing the card 20 are folded inward to overlap the top flap 36 at each end 38, and the connection cable 34 at the one end. As with the top flap 36, each side flap 40 includes an adhesive on the inner surface of each flap 40 such that each side flap 40 adheres to each top flap 36 at each end 38 of the housing 100 containing the card 20, and the connection cable 34 at one end 38 of the card 20, during assembly. Each bottom flap 42 is then folded upward to overlap the top 36 and side flaps 40, as well as the connection cable 34 (at the one end 38 of the card 20), as illustrated in Fig. 7. As with the top and side flaps 36, 40, each bottom flap 42 includes an adhesive on the inner surface of the flap 42 to adhere each bottom flap 42 to the connection cable 34 and/or the side and top

flaps 36, 40.

It should be noted that the present invention is not intended to be limited to the order of folding the tamper respondent cloth 10 around the card 20 described above. In contrast, the side flaps 40 may be folded inward first, followed by either the top 36 or bottom flaps 42. Alternatively, the bottom flap 42 may be folded upward first, followed by either the side flaps 40 or the top flap 36, and so on.

The enclosure 44, having fold lines 45 at each end 38 thereof, is then placed in a clamping device or fixture 46 similar to the one shown in Fig. 9. The clamping device 46 includes a base 48 and a plurality of legs 50 thereunder. A stationary clamping arm 52 is securely mounted to a first end of the base 48. A traversing clamping arm 54 is slidably mounted to the base 48. A biasing or traversing mechanism 56, located at a second end of the base 48, is connected to the traversing clamping arm 54. The traversing mechanism 56, comprising a biasing screw, a hydraulic mechanism, an electro-mechanical sensor motor, etc., functions to bias the traversing clamping arm 54 toward and/or away from the stationary clamping arm 52.

In practice, the enclosure 44 is placed on the base 48 of the clamping device 46, such that one end 56 of the enclosure 44 is positioned against the stationary clamping arm 52. The traversing clamping arm 54 is then biased toward the other end 56 of the enclosure 44 via the biasing mechanism 56.

Once the traversing clamping arm 54 of the clamping device 46 is adjusted such that the enclosure 44 fits snugly between the traversing clamping arm 54 and the stationary clamping arm 52, the enclosure 44 and clamping device 46 are exposed to a temperature of approximately 40-90 °C, and preferably between 50-70 °C (because the ink lines 14 may begin to soften and reflow at temperatures above approximately 80 °C), 60 °C being the optimal temperature, for approximately 1 hour (refer to the temperature chart of Fig. 8). The enclosure 44 is then removed from the clamping device 46. Thereafter, the enclosure 44 may undergo additional processing as known in the art, i.e., applying a polyurethane coating, etc.

Heating the tamper respondent cloth 10 initially causes the layers of adhesive to soften, thereby allowing the pierce and laser respondent layer to slide past the

delamination respondent layer in the fold areas such that the cloth 10 bends more easily. Upon continued heating the adhesive cross-links or cures due to thermal aging, thereby making the adhesive become more solidified. After removing the heat, the adhesive continues to harden in the folded position during cooling. As a result, the folded cloth 10 forming the enclosure exhibits improved fold retention and reduced stress. And unlike the previous methods of forming enclosures, the cloth 10 does not come un-wrapped during processing. Accordingly, the subsequent encapsulant material, e.g., a polyurethane coating, will not flow past the folds into the inner enclosure to damage the cryptographic processor card 20, as often happens with conventional methods.

It should be noted that the enclosure 44 described and illustrated herein is only one example of the type of enclosure that may be use in combination with the present invention. The present invention is in no way intended to be limited to use in conjunction with electronic assemblies of this size, shape and form. Rather, the enclosure may take the form of a wedge-shaped enclosure, a cuboid, a cube, etc.

While this invention has been described in conjunction with the specific embodiments outlined above, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, the
5 embodiments of the invention as set forth above are intended to be illustrative, not limiting. Various changes may be made without departing from the spirit and scope of the invention as defined in the following claims.

CLAIMS

We claim:

1 1. A method of forming a security enclosure, comprising:
2 providing an electronic assembly;
3 enclosing the assembly in a tamper respondent wrap,
4 such that the wrap forms fold lines at a first and second
5 end of the assembly;
6 placing the enclosed assembly in a fixture, wherein the
7 fixture comprises a base upon which the assembly rests, a
8 first stationary arm mounted on the base holding the fold
9 lines at the first end of the assembly, a second arm
10 slidably mounted on the base, and a traversing mechanism to
11 bias the second arm toward the fold lines at the second end
12 of the assembly; and
13 heating the enclosed assembly.

1 2. The method of claim 1, further comprising heating the
2 enclosed assembly at a temperature of approximately 60 °C.

1 3. The method of claim 1, further comprising heating the
2 enclosed assembly at a temperature of approximately 40-90
3 °C.

1 4. The method of claim 1, further comprising heating the
2 enclosed assembly for approximately 1 hour.

1 5. The method of claim 1, wherein the fixture comprises a
2 clamping device.

1 6. The method of claim 1, wherein the tamper respondent wrap
2 comprises a flexible material having tamper respondent
3 detection devices.

1 7. The method of claim 1, wherein the tamper respondent wrap
2 comprises:

3 at least one pierce and laser respondent layer;
4 a delamination respondent layer; and
5 an adhesive between the pierce and laser respondent
6 layer and the delamination respondent layer.

1 8. The method of claim 7, wherein the pierce and laser
2 respondent layer and the delamination respondent layer
3 comprise a plurality of ink lines on at least one side of
4 the pierce and laser respondent layer and the delamination
5 respondent layer.

1 9. The method of claim 1, wherein the electronic assembly
2 comprises a cryptographic processor.

1 10. The method of claim 9, wherein the cryptographic
2 processor comprises a printed circuit board, having mounted
3 thereon:

4 an encryption module to carry secured sensitive
5 information;

6 a memory to store a key necessary to access the
7 information;

8 an erase circuit to erase the information in the
9 encryption module in the event the tamper respondent wrap is
10 breached; and

11 an enclosure monitor to activate the erase circuit in
12 the event a breach is detected.

1 11. A method of producing a tamper respondent enclosure,
2 comprising:
3 enclosing a cryptographic processor in a tamper
4 respondent sheet, wherein an adhesive material secures the
5 enclosure;
6 holding the enclosed cryptographic processor such that
7 the adhesive material remains intact; and
8 applying heat to the enclosed cryptographic processor
9 to strengthen the adhesive material.

1 12. The method of claim 11, further including holding the
2 enclosed cryptographic processor in a clamping device.

1 13. The method of claim 11, further including applying heat
2 at a temperature of approximately 60 °C.

1 14. The method of claim 11, further including applying heat
2 at a temperature of approximately 50-70 °C.

1 15. A method of forming a security enclosure, comprising:
2 providing a circuit card;
3 enclosing the card in a tamper respondent cloth,
4 wherein an adhesive secures fold lines of the cloth;
5 holding the fold lines of the cloth to maintain
6 adhesive contact; and
7 heating the enclosed card.

1 16. The method of claim 15, further comprising holding the
2 cloth in a clamping device to maintain the adhesive contact.

1 17. The method of claim 16, wherein the clamping device
2 comprises:

3 a base upon which a security enclosure rests;
4 a first stationary arm mounted on the base, which holds
5 a first end of the security enclosure;
6 a second arm slidably mounted on the base; and
7 a traversing mechanism to bias the second arm toward a
8 second end of the security enclosure.

18. The method of claim 15, further comprising heating the enclosed card at approximately 60 °C for approximately 1 hour.

19. The method of claim 15, further comprising curing the adhesive.

20. The method of claim 15, wherein the circuit card comprises a cryptographic processor.

END9-2000-0078-US1

1 21. A method of assembling a security enclosure comprising:
2 providing a fixture;
3 providing an enclosure having a cloth member thereon;
4 placing the enclosure in the fixture;
5 heating the enclosure; and
6 removing the enclosure from the fixture.

1 22. The method of claim 21, wherein the fixture comprises a
2 clamping device.

1 23. The method of claim 22, wherein the clamping device
2 comprises:

3 a base upon which a security enclosure rests;
4 a first stationary arm mounted on the base, which holds
5 a first end of the security enclosure;
6 a second arm slidably mounted on the base; and
7 a traversing mechanism to bias the second arm toward a
8 second end of the security enclosure.

1 24. The method of claim 21, wherein the enclosure comprises
2 a circuit assembly having a tamper respondent cloth wrapped
3 therearound.

1 25. The method of claim 21, wherein heating comprises
2 exposing the enclosure to a temperature of approximately 50-
3 70 °C for about 1 hour.

END9-2000-0078-US1

1 26. An apparatus for securing a security enclosure,
2 comprising;
3 a base upon which a security enclosure rests;
4 a first stationary arm mounted on the base, which holds
5 a first end of the security enclosure;
6 a second arm slidably mounted on the base; and
7 a traversing mechanism to bias the second arm toward a
8 second end of the security enclosure.

END9-2000-0078-US1

METHOD AND APPARATUS FOR IMPROVED FOLD
RETENTION ON A SECURITY ENCLOSURE

ABSTRACT OF THE DISCLOSURE

A method and apparatus for forming a security enclosure
5 having improved fold retention. In particular, the
enclosure is formed by folding a flexible tamper respondent
cloth around an electronic assembly. An adhesive on the
inner folded surfaces of the cloth temporarily retains the
folds. The enclosure is then exposed to heat and pressure
10 to promote improved adhesion strength of the adhesive,
thereby improving fold retention.




Fig. 1

2/5
Butturini et al.
END9-2000-0078-US1 LRF




FIG. 2A

3/5
Butturini et al.
END9-2000-0078-US1 LRF




FIG. 2B

Fig 3




Fig 4




Fig 5




Fig 6





Fig 7



Bending Modulus of Tamper Respondent Cloth




Fig 8




Fig. 9

Docket No.
END9-2000-0078-US1

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD AND APPARATUS FOR IMPROVED FOLD RETENTION ON A SECURITY ENCLOSURE

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as United States Application No. or PCT International Application Number _____ and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

(Number)

(Country)

(Day/Month/Year Filed)

☐

(Number)

(Country)

(Day/Month/Year Filed)

☐

(Number)

(Country)

(Day/Month/Year Filed)

☐

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

David L. Adour-29,604

Lawrence R. Fraley-26,885

John R. Pivnichny-43,001

Arthur J. Samodovitz-31,297

William H. Steinberg-28,540

Christopher A. Hughes-26,914

Edward A. Pennington-32,588

John E. Hoel-26,279

Joseph C. Redmond, Jr.-18,753

Send Correspondence to: Customer No.: 5409

Direct Telephone Calls to: (name and telephone number)

Kristen L. Ashdown- (518) 220-1850

Full name of sole or first inventor

Giuseppe Butturini

Sole or first inventor's signature

Butturini Giuseppe

Date

8-22-2000

Residence

Via Monte Grappa 11, 20044 Bernareggio (MI), Italy

Citizenship

Italian

Post Office Address

Same as Residence

Full name of second inventor, if any

Mario L. Cesana

Second inventor's signature

Mario L. Cesana

Date

8/21/2000

Residence

Via C: Guidion 42/E, 20045 Besana in Brianza, Italy

Citizenship

Italian

Post Office Address

Same as Residence

Full name of third inventor, if any Donald S. Farquhar	Date
Third inventor's signature <i>Donald S Farquhar</i>	<i>August 10, 2000</i>
Residence 1106 Rodman Road, Endicott, NY 13760	
Citizenship USA	
Post Office Address Same as Residence	

Full name of fourth inventor, if any Fulvio Fontana	Date
Fourth inventor's signature <i>Fulvio Fontana</i>	<i>August 22, 2000</i>
Residence Via Montebianco 8/c, 20052 Monza, Italy	
Citizenship Italian	
Post Office Address Same as Residence	

Full name of fifth inventor, if any	Date
Fifth inventor's signature	
Residence	
Citizenship	
Post Office Address	

Full name of sixth inventor, if any	Date
Sixth inventor's signature	
Residence	
Citizenship	
Post Office Address	